

Series D



Axial fans for exhaust ventilation

- Motor type: AC
- Casing material: Plastic
- Timer: Turn off timer
- Humidity sensor

Lineup	Connected air duct size, mm	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer
 100 D	100	95	34	×	×	×
 100 D turbo	100	124	37	×	×	×
 100 D 12	100	86	33	×	×	×
 100 D L	100	95	34	×	×	×
 100 D K	100	95	34	×	×	×
 100 D K L	100	95	34	×	×	×
 100 D K L turbo	100	124	37	×	×	×

	100 D K 12	100	86	33	✗	✗	✗
	100 D T	100	95	34	✗	✗	✓
	100 D T turbo	100	124	37	✗	✗	✗
	100 D T L	100	95	34	✗	✗	✓
	100 D T K	100	95	34	✗	✗	✓
	100 D T K L	100	95	34	✗	✗	✓
	100 D TH	100	95	34	✗	✓	✓
	100 D TH turbo	100	124	37	✗	✓	✓
	100 D TH L	100	95	34	✗	✓	✓
	100 D TH K	100	95	34	✗	✓	✓
	100 D TH K turbo	100	124	37	✗	✓	✓
	100 D TH K L	100	95	34	✗	✓	✓
	100 D V	100	95	34	✓	✗	✗
	100 D V turbo	100	124	37	✓	✗	✗

	100 D VL	100	95	34	✓	✗	✗
	100 D VK	100	95	34	✓	✗	✗
	100 D VTH	100	95	34	✓	✓	✓
	120 D	120	174	36	✗	✗	✗
	120 D V	120	174	36	✓	✗	✗
	125 D	125	180	35	✓	✓	✓
	125 D turbo	125	226	37	✗	✗	✗
	125 D 12	125	165	34	✗	✗	✗
	125 D L	125	180	35	✓	✓	✓
	125 D K	125	180	35	✓	✓	✓
	125 D KL	125	180	35	✓	✓	✓
	125 D K turbo	125	226	37	✗	✗	✗
	125 D T	125	180	35	✓	✓	✓
	125 D TL	125	180	35	✓	✓	✓

	125 D T K	125	180	35	✓	✓	✓
	125 D TH	125	180	35	✓	✓	✓
	125 D TH L	125	180	35	✓	✓	✓
	125 D TH K	125	180	35	✓	✓	✓
	125 D V	125	180	35	✓	✓	✓
	125 D VTH	125	180	35	✓	✓	✓
	150 D	150	292	38	✗	✓	✓
	150 D turbo	150	341	40	✗	✗	✗
	150 D 12	150	260	37	✗	✗	✗
	150 D L	150	292	38	✗	✓	✓
	150 D L turbo	150	341	40	✗	✗	✗
	150 D K	150	292	38	✗	✓	✓
	150 D K L	150	292	38	✗	✓	✓
	150 D T	150	292	38	✗	✓	✓

	150 D TL	150	292	38	✗	✓	✓
	150 D TL turbo	150	341	40	✗	✗	✓
	150 D TK	150	292	38	✗	✓	✓
	150 D TH	150	292	38	✗	✓	✓
	150 D TH K	150	292	38	✗	✓	✓
	150 D TH KL	150	292	38	✗	✓	✓
	150 D V	150	292	38	✓	✓	✓
	150 D VK	150	292	38	✓	✓	✓
	150 D VT	150	292	38	✓	✓	✓