


















Series M1



Axiale Abluftventilatoren

- Motortyp: AC
- Gehäusematerial: Plastic
- Timer: Turn off timer
- Feuchtigkeitssensor
- Bewegungssensor

Lineup	Luftkanalgröße, mm	Leistung, W	Max. Förderleistung, m ³ /h	Schalldruckpegel LpA @ 3 m, dB(A)	Bewegungssensor	Feuchtigkeitssensor	Timer
 100 M1	100	14	98	34	×	×	×
 100 M1 turbo	100	16	128	37	×	×	×
 100 M1 press	100	16	99	37	×	×	×
 100 M1 12	100	14	86	33	×	×	×
 100 M1 L	100	14	98	34	×	×	×
 100 M1 T L	100	14	98	34	×	×	✓
 100 M1 TH	100	14	98	34	×	✓	✓

	100 M1 TP	100	14	98	34	✓	✗	✓
	125 M1	125	16	185	35	✗	✗	✗
	125 M1 turbo	125	22	232	40	✗	✗	✗
	125 M1 press	125	22	188	39	✗	✗	✗
	125 M1 12	125	16	165	34	✗	✗	✗
	125 M1 L	125	16	185	35	✗	✗	✗
	125 M1 T L	125	16	185	35	✗	✗	✗
	150 M1	150	24	295	39	✗	✗	✗
	150 M1 press	150	29	307	41	✗	✗	✗
	150 M1 L	150	24	295	39	✗	✗	✗