



















Series **MPA E EC A31**



- Filter: Coarse 90% / G4 (Option ePM1 70% / F7)
- In schallgedämmtem Gehäuse
- Motortyp: EC
- BMS-Protokoll: Modbus

Lineup	Maximale Versorgungsspannung, V	Nennleistung, W	Maximaler Volumenstrom bei 50 Hz, m ³ /h	Schalldruckpegel LpA bei 3 m, dB(A)
 MPA 300 E-1.7 EC A31	230	64	365	35
 MPA 300 E-5.1 EC A31	230	64	354	35
 MPA 400 E-2.4 EC A31	230	62	430	31
 MPA 400 E-3.3 EC A31	230	62	430	31
 MPA 400 E-6.0 EC A31	400	62	430	31
 MPA 700 E-3.0 EC A31	400	116	760	41
 MPA 700 E-6.0 EC A31	400	116	760	41

 MPA 700 E-9.0 EC A31	400	116	760	41
 MPA 1000 E-6.0 EC A31	400	165	1000	45
 MPA 1000 E-12.0 EC A31	400	165	1000	45
 MPA 1000 E-15.0 EC A31	400	165	1000	45
 MPA 1500 E-9.0 EC A31	400	223	1500	46
 MPA 1500 E-14.0 EC A31	400	223	1500	46
 MPA 1500 E-18.0 EC A31	400	223	1500	46
 MPA 2000 E-12.0 EC A31	400	406	2450	48
 MPA 2000 E-18.0 EC A31	400	406	2450	48
 MPA 2000 E-24.0 EC A31	400	406	2450	48
 MPA 3000 E-18.0 EC A31	400	472	3150	47
 MPA 3000 E-27.0 EC A31	400	472	3150	47
 MPA 3000 E-45.0 EC A31	400	472	3150	47
 MPA 4000 E-24.0 EC A31	400	717	5000	49

 MPA 4000 E-45.0 EC A31	400	717	5000	49
 MPA 4000 E-54.0 EC A31	400	717	5000	49