
























Series **OVK**


Niederdruck-Axialventilatoren im Stahlgehäuse für Wandmontage

- Motortyp: AC
- Laufradtyp: Axial
- Gehäusematerial: Coated steel

Lineup	Luftkanalgröße, mm	Leistung, W	Max. Förderleistung, m <sup>3</sup> /h
 OVK 2D 250	250	80	1060
 OVK 2D 300	300	145	2310
 OVK 4D 250	250	60	850
 OVK 4D 300	300	75	1310
 OVK 4D 350	350	140	2350
 OVK 4D 400	400	180	3740
 OVK 4D 450	450	250	5280

 OVK 4D 500	500	450	6570
 OVK 4D 550	550	750	9700
 OVK 4D 630	630	800	12200
 OVK 2E 200	200	55	860
 OVK 2E 250	250	80	1050
 OVK 2E 300	300	145	2230
 OVK 4E 250	250	50	800
 OVK 4E 300	300	75	1340
 OVK 4E 350	350	140	2500
 OVK 4E 400	400	180	3580
 OVK 4E 450	450	250	4680
 OVK 4E 500	500	420	7060
 OVK 4E 550	550	550	8800
 OVK 4E 630	630	750	11900

 OVK 6D 710	710	1150	15440
 OVK 6D 800	800	1850	25000