


















Series **S**


Axiale Abluftventilatoren

- Motortyp: AC
- Gehäusematerial: Plastic
- Timer: Turn off timer
- Feuchtigkeitssensor

Lineup	Luftkanalgröße, mm	Max. Förderleistung, m ³ /h	Schalldruckpegel LpA @ 3 m, dB(A)	Zugschnur	Feuchtigkeitssensor	Timer	Elektrische Eingangsleistung, W
 100 S	100	95	34	✗	✗	✗	14
 100 S K	100	95	34	✗	✗	✗	
 100 ST	100	95	34	✗	✗	✓	14
 100 ST L	100	95	34	✗	✗	✓	
 100 S L	100	95	34	✗	✗	✗	
 100 S V	100	95	34	✓	✗	✗	14
 100 S V L	100	95	34	✓	✗	✗	
 100 S TH L	100	95	34	✗	✓	✓	

 100 S 12	100	86	33	×	×	×	14
 100 S turbo	100	124	37	×	×	×	16
 100 S (120V/60Hz)	100			×	×	×	
 125 S	125	180	35	×	×	×	16
 125 S turbo	125	226	37	×	×	×	24
 125 S 12	125	165	34	×	×	×	16
 150 S	150	292	38	×	×	×	24
 150 S turbo	150	341	40	×	×	×	30
 150 S 12	150	260	37	×	×	×	24