


















Series **S**


Axiale Abluftventilatoren

- Motortyp: AC
- Timer: Nachlaufschalter
- Feuchtigkeitssensor

Lineup	Luftkanalgröße, mm	Leistung, W	Max. Förderleistung, m ³ /h	Schalldruckpegel LpA @ 3 m, dB(A)	Zugschnur	Feuchtigkeitssensor	Timer
 100 S	100	14	95	34	✗	✗	✗
 100 S K	100	14	95	34	✗	✗	✗
 100 S T	100	14	95	34	✗	✗	✓
 100 S T L	100	14	95	34	✗	✗	✓
 100 S L	100	14	95	34	✗	✗	✗
 100 S V	100	14	95	34	✓	✗	✗
 100 S V L	100	14	95	34	✓	✗	✗

 100 S TH L	100	14	95	34	×	✓	✓
 100 S 12	100	14	86	33	×	×	×
 100 S turbo	100	16	124	37	×	×	×
 100 S (120V/60Hz)	100				×	×	×
 125 S	125	16	180	35	×	×	×
 125 S turbo	125	24	226	37	×	×	×
 125 S 12	125	16	165	34	×	×	×
 150 S	150	24	292	38	×	×	×
 150 S turbo	150	30	341	40	×	×	×
 150 S 12	150	24	260	37	×	×	×