























Series X1



Axiale Abluftventilatoren

- Motortyp: AC
- Gehäusematerial: Plastic
- Timer: Turn off timer
- Feuchtigkeitssensor

Lineup	Luftkanalgröße, mm	Max. Förderleistung, m ³ /h	Schalldruckpegel LpA @ 3 m, dB(A)	Zugschnur	Feuchtigkeitssensor	Timer	Elektrische Eingangsleistung, W
 100 X1	100	99	33	×	×	×	14
 100 X1 K	100	99	33	×	×	×	
 100 X1 L	100	99	33	×	×	×	
 100 X1 turbo	100	129	37	×	×	×	16
 100 X1 12	100	86	33	×	×	×	14
 100 X1 K 12	100	86	33	×	×	×	
 100 X1 L turbo	100	129	37	×	×	×	
 125 X1	125	185	34	×	×	×	16

 125 X1 V	125	185	34	✓	✗	✗	
 125 X1 K	125	185	34	✗	✗	✗	
 125 X1 L	125	185	34	✗	✗	✗	
 125 X1 T	125	185	34	✗	✗	✓	
 125 X1 TH	125	185	34	✗	✓	✓	
 125 X1 L turbo	125	232	37	✗	✗	✗	
 125 X1 turbo	125	232	37	✗	✗	✗	24
 125 X1 12	125	160	34	✗	✗	✗	16
 150 X1	150	295	37	✗	✗	✗	24
 150 X1 (220V/60Hz)	150			✗	✗	✗	
 150 X1 K	150	295	37	✗	✗	✗	
 150 X1 L	150	295	37	✗	✗	✗	
 150 X1 turbo	150	345	41	✗	✗	✗	29
 150 X1 L turbo	150	345	41	✗	✗	✗	