























Series **X1**


Axiale Abluftventilatoren

- Motortyp: AC
- Timer: Turn off timer
- Feuchtigkeitssensor

Lineup	Luftkanalgröße, mm	Leistung, W	Max. Förderleistung, m ³ /h	Schalldruckpegel LpA @ 3 m, dB(A)	Zugschnur	Feuchtigkeitssensor	Timer
 100 X1	100	14	99	33	×	×	×
 100 X1 K	100	14	99	33	×	×	×
 100 X1 L	100	14	99	33	×	×	×
 100 X1 turbo	100	16	129	37	×	×	×
 100 X1 12	100	14	86	33	×	×	×
 100 X1 K 12	100	14	86	33	×	×	×
 100 X1 L turbo	100	16	129	37	×	×	×

 125 X1	125	16	185	34	×	×	×
 125 X1 V	125	16	185	34	✓	×	×
 125 X1 K	125	16	185	34	×	×	×
 125 X1 L	125	16	185	34	×	×	×
 125 X1 T	125	16	185	34	×	×	✓
 125 X1 TH	125	16	185	34	×	✓	✓
 125 X1 L turbo	125	24	232	37	×	×	×
 125 X1 turbo	125	24	232	37	×	×	×
 125 X1 12	125	16	160	34	×	×	×
 150 X1	150	24	295	37	×	×	×
 150 X1 (220V/60Hz)	150				×	×	×
 150 X1 K	150	24	295	37	×	×	×
 150 X1 L	150	24	295	37	×	×	×
 150 X1 turbo	150	29	345	41	×	×	×
 150 X1 L turbo	150	29	345	41	×	×	×