























Series X1



Axiale Abluftventilatoren

- Motortyp: AC
- Gehäusematerial: Plastic
- Timer: Turn off timer
- Feuchtigkeitssensor

| Lineup | Luftkanalgröße, mm | Leistung, W | Max. Förderleistung, m ³ /h | Schalldruckpegel LpA @ 3 m, dB(A) | Zugschnur | Feuchtigkeitssensor | Timer |
|--|--------------------|-------------|--|-----------------------------------|-----------|---------------------|-------|
|  100 X1 | 100 | 14 | 99 | 33 | × | × | × |
|  100 X1 K | 100 | 14 | 99 | 33 | × | × | × |
|  100 X1 L | 100 | 14 | 99 | 33 | × | × | × |
|  100 X1 turbo | 100 | 16 | 129 | 37 | × | × | × |
|  100 X1 12 | 100 | 14 | 86 | 33 | × | × | × |
|  100 X1 K 12 | 100 | 14 | 86 | 33 | × | × | × |
|  100 X1 L turbo | 100 | 16 | 129 | 37 | × | × | × |

| | | | | | | | |
|--|-----|----|-----|----|---|---|---|
|  125 X1 | 125 | 16 | 185 | 34 | × | × | × |
|  125 X1 V | 125 | 16 | 185 | 34 | ✓ | × | × |
|  125 X1 K | 125 | 16 | 185 | 34 | × | × | × |
|  125 X1 L | 125 | 16 | 185 | 34 | × | × | × |
|  125 X1 T | 125 | 16 | 185 | 34 | × | × | ✓ |
|  125 X1 TH | 125 | 16 | 185 | 34 | × | ✓ | ✓ |
|  125 X1 L turbo | 125 | 24 | 232 | 37 | × | × | × |
|  125 X1 turbo | 125 | 24 | 232 | 37 | × | × | × |
|  125 X1 12 | 125 | 16 | 160 | 34 | × | × | × |
|  150 X1 | 150 | 24 | 295 | 37 | × | × | × |
|  150 X1 (220V/60Hz) | 150 | | | | × | × | × |
|  150 X1 K | 150 | 24 | 295 | 37 | × | × | × |
|  150 X1 L | 150 | 24 | 295 | 37 | × | × | × |
|  150 X1 turbo | 150 | 29 | 345 | 41 | × | × | × |
|  150 X1 L turbo | 150 | 29 | 345 | 41 | × | × | × |