

MV 150 V Series



Modifications

Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation systems.
- Used for correct air flow distribution in premises.
- Wall or ceiling mounting.

Design

- Made of quality and durable plastic.
- Multi-element structure. The internal part is fixed to the base with latches for easy cleaning without dismantling.
- Screw fixing.
- The grille has slanted vanes.

Colour modifications



MV 150 V – model with a round flange (V)



- Fitted with a round connecting flange for mounting with Ø 150 mm air duct.
- Suitable for direct mounting with VENTS VKO 150 fan.
- **MV 150 Vs** – model with a round flange and a protecting insect screen.



MV 150 VR – model with a round flange and air flow regulator (VR)



- Fitted with a round connecting flange for mounting with Ø 150 mm air duct.
- Equipped with a movable flap for air flow regulation.
- Air pass is regulated with a tilt wand or pull cords.
- Suitable for direct mounting with VENTS VKO 150 fan.
- **MV 150 VRs** – model with a round flange, air flow regulator and a protecting insect screen.



Overall dimensions

Model	Dimensions [mm]					Air pass, [m ²]	Fig. no.
	□B	□H	L	L1	D		
MV 150 V	186	142	15	50	150	0.0083	1, 2
MV 150 VR	186	142	15	50	150	0.0044	1, 2




Fig. 1




Fig. 2