

MV 100 bV ASA MV 125 bV ASA MV 150 bV ASA Series



Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation systems.
- Used for correct air flow distribution in premises.
- Wall or ceiling mounting.

Design

- Made of quality and durable plastic.
- Fixing with screws or glue.
- Modifications with air flow regulator and a protecting insect screen are available.

Colour modifications



Modifications

MV 100 bV ASA, MV 125 bV ASA, MV 150 bV ASA – round grilles with a flange (bV)



- Fitted with a round connecting flange for mounting to \varnothing 100 mm (MV 100 bV ASA), \varnothing 125 mm (MV 125 bV ASA) or \varnothing 150 mm (MV 150 bV ASA) air ducts.
- MV 100 bVs ASA, MV 125 bVs ASA, MV 150 bVs ASA – models with a protecting insect screen.



MV 100 bVR ASA – models with a round flange and air flow regulator (bVR)



- Fitted with a round connecting flange for mounting to \varnothing 100 mm.
- Equipped with a movable flap for air flow regulation with a slider.
- MV 100 bVRs ASA – with a protecting insect screen.



MV 125 bVRD ASA, MV 150 bVRD ASA – models with air flow regulator and four-element connecting flange (bVRD)



- Equipped with four-element connecting flange with adjustable diameter for connection to \varnothing 100-125 mm (MV 125 bVRD ASA) and \varnothing 100-150 mm (MV 150 bVRD ASA) round air ducts.
- Equipped with a movable flap for air flow regulation with a slider.



Overall dimensions

Model	Dimensions [mm]				Air pass, [m ²]	Fig. no.
	L	B	D1	D		
MV 100 bV ASA	29	118	100	128	0.004	1, 2
MV 100 bVR ASA	29	118	100	128	0.005	1, 3
MV 125 bV ASA	29	148	125	160	0.0065	1, 2
MV 125 bVRD ASA	45	148	100-125	160	0.005	1, 4
MV 150 bV ASA	29	176	150	200	0.01	1, 2
MV 150 bVRD ASA	45	176	100-150	200	0.005	1, 4




Fig. 1




Fig. 3




Fig. 2




Fig. 4