

MV 160 Series



Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation systems.
- Used for correct air flow distribution in premises.
- Wall or ceiling mounting.

Design

- Made of quality and durable plastic.
- Multi-element structure. The internal part is fixed to the base with latches for easy cleaning without dismantling.
- Fixing with screws or lugs depending on grille modification.

Colour modifications



Modifications

MV 160 – basic modification



- Screw fixing.
- **MV 160 s** – model with a protecting insect screen and screw fixing.
- **MV 160 M** – model with fixing lugs.
- **MV 160 Ms** – model with fixing lugs and a protecting insect screen.



MV 160 VD – model with four-element connecting flange (VD)



- Screw fixing.
- Equipped with four-element connecting flange with adjustable diameter for connection to \varnothing 100-150 mm round air duct.
- **MV 160 VDs** – model with four-element connecting flange and a protecting insect screen.
- **MV 160 VDM** – model with four-element connecting flange and fixing lugs.
- **MV 160 VDMs** – model with four-element connecting flange, fixing lugs and a protecting insect screen.



Overall dimensions

Model	Dimensions [mm]							Air pass, [m ²]	Fig. no.
	H	B	L	L1	H1	B1	D		
MV 160	299	221	15	–	283	205	–	0.026	1, 2
MV 160 VD	299	221	15	42	283	205	100-150	0.026	1, 3




Fig. 1




Fig. 2




Fig. 3