




MPA 300 E-5.1 EC A31



Air supply units in the sound- and heat-insulated casing


- Power of electrical reheater: 5100
- Maximum airflow: 354
- Sound pressure level LpA at 3 m: 35
- Filter: Coarse 90% / G4 (option ePM1 70% / F7)
- Sound insulation
- Motor type: EC
- Reheater: Electric
- BMS protocol: ModBus
- Control: Wired control panel
- Casing material: Aluzinc steel

	Unit of measurement	MPA 300 E-5.1 EC A31
Connected air duct size	mm	160
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	64
Power of electrical reheater	W	5100
Unit current	A	7.4
Maximum airflow	m ³ /h	354
Sound pressure level LpA at 3 m	dB(A)	35
Weight	kg	24
Filter	-	Coarse 90% / G4 (option ePM1 70% / F7)
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP44





Dimensions

D	H	L	L1	L2	W	W1	W2
160	290	850	903	950	400	514	313




Accessories



Other accessories


Name	Photo	Description
SF 334x226x48 G4		Panel filter G4
SF 334x226x48 F7		F7 panel filter

Other accessories

Name	Photo	Description
VVG 125		Flexible anti-vibration inserts for round ducts

For round ducts



Name	Photo	Description
SR 125/600		Silencers made of galvanized steel filled with non-combustible sound-absorbing material
SR 125/900		Silencers made of galvanized steel filled with non-combustible sound-absorbing material

SR 125/1200		Silencers made of galvanized steel filled with non-combustible sound-absorbing material
-----------------------------	-----------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------

For round ducts

Name	Photo	Description
KRV 125		Air dampers for automatic air flow control in round ducts

Electric actuators

Name	Photo	Description
Belimo TF230		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions
Belimo TF24		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions