

100 MA press



Axial fans with automatic louver shutters for exhaust ventilation


- Maximum airflow: 99
- Sound pressure level LpA at 3 m: 37
- Motor type: AC
- Casing material: Plastic

	Unit of measurement	100 MA press
Connected air duct size	mm	100
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	20
Unit current	A	0.1
Maximum airflow	m ³ /h	99
Sound pressure level LpA at 3 m	dB(A)	37
Weight	kg	0.65
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IP24
ErP compliance	-	2016
Cold - Specific energy consumption (SEC)	kWh/(m ² /a)	29
SEC Class Cold	-	B
Average - Specific energy consumption (SEC)	kWh/(m ² /a)	13
SEC Class Average	-	E
Warm - Specific energy consumption (SEC)	kWh/(m ² /a)	4
SEC Class Warm	-	F
Unit category	-	RVU

Type of ventilation unit	-	Unidirectional
Type of drive installed	-	Multi-speed
Type of heat recovery system	-	None
Maximum flow rate	m ³ /h	99
Electric power input	W	20
Reference flow rate	m ³ /s	0.019
Specific power input (SPI)	W/(m ³ /h)	0.13
Control typology	-	Manual control
Maximum external leakage rates	%	2.7
Cold - The annual electricity consumption (AEC)	kWh/a	200
Average - The annual electricity consumption (AEC)	kWh/a	200
Warm - Jährlicher Stromverbrauch (JSV)	kWh/a	200
Cold - The annual heating saved (AHS)	kWh/a	3400
The annual heating saved (AHS) Average	kWh/a	1700
The annual heating saved (AHS) Warm	kWh/a	800
Sound power level	dB(A)	57
Declared typology	-	RVU UVU

Dimensions

∅D	B	B1	B2	H	L	L1
100	165	150	150	150	92	32



Accessories

Cooker Hoods

Name	Photo	Description
------	-------	-------------

[FO_100](#)



The window flange applicable for all VENTS fans except for VKO, VKO1, iFan, Quiet, MAO, CF