

# 100 MA V



Axial fans with automatic louver shutters for exhaust ventilation

- Maximum airflow: 98
- Sound pressure level LpA at 3 m: 34
- Motor type: AC
- Casing material: Plastic
- Pull cord

|                                 | Unit of measurement | 100 MA V |
|---------------------------------|---------------------|----------|
| Connected air duct size         | mm                  | 100      |
| Speed                           | -                   | 1        |
| Minimum supply voltage          | V                   | 220      |
| Maximum supply voltage          | V                   | 240      |
| Power supply frequency          | Hz                  | 50       |
| Rated power                     | W                   | 18       |
| Unit current                    | A                   | 0.085    |
| Maximum airflow                 | m <sup>3</sup> /h   | 98       |
| Sound pressure level LpA at 3 m | dB(A)               | 34       |
| Weight                          | kg                  | 0.65     |
| Ambient air temperature min     | °C                  | 1        |
| Ambient air temperature max     | °C                  | 40       |
| Ingress protection rating       | -                   | IP24     |




### Dimensions

| <b>∅D</b> | <b>B</b> | <b>B1</b> | <b>B2</b> | <b>H</b> | <b>L</b> | <b>L1</b> |
|-----------|----------|-----------|-----------|----------|----------|-----------|
| 100       | 165      | 150       | 150       | 150      | 92       | 32        |



## Accessories

### Flanges

| Name                   | Photo  | Description  |
|------------------------|--|--|
| <a href="#">FO_100</a> |  | The window flange applicable for all VENTS fans except for VKO, VKO1, iFan, Quiet, MAO, CF |