


# 100 MF TH L



Low-noise and energy saving axial fan for exhaust ventilation


- Maximum airflow: 90
- Sound pressure level LpA at 3 m: 29
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Humidity sensor
- Timer: Turn off timer

	Unit of measurement	100 MF TH L
Connected air duct size	mm	100
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	8
Unit current	A	0.05
Maximum airflow	m <sup>3</sup> /h	90
Sound pressure level LpA at 3 m	dB(A)	29
Weight	kg	0.45
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IP44




### Dimensions

<b>∅D</b>	<b>B</b>	<b>L</b>	<b>L1</b>
99	150	79	19




## Accessories

### Cooker Hoods

Name	Photo	Description
<a href="#">FO 100</a>		The window flange applicable for all VENTS fans except for VKO, VKO1, iFan, Quiet, MAO, CF

## Ecodesign



Trademark	Vents			
Model	100 MF TH L			
Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a))	Cold	Average	Warm	
	53.6	A+ 26.5	B 11	E
Type of ventilation unit	Unidirectional			
Type of drive installed	Single speed			
Type of heat recovery system	None			
Maximum flow rate (m <sup>3</sup> /h)	90			
Electric power input (W)	8			
Reference flow rate (m <sup>3</sup> /s)	0.018			
Specific power input (SPI) (W/(m <sup>3</sup> /h))	0.089			
Control typology	Local demand control			
Maximum external leakage rates (%)	2.7			
Sound power level (dB(A))	49			
Declared typology	RVU UVU			
The annual electricity consumption (AEC) (kWh/a)	Cold	Average	Warm	
	72	72	72	
The annual heating saved (AHS) (kWh/a)	Cold	Average	Warm	
	5536	2830	1280	