

125 D K turbo



Axial fans for exhaust ventilation

- Maximum airflow: 226
- Sound pressure level LpA at 3 m: 37
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper

| | Unit of measurement | 125 D K turbo |
|---------------------------------|---------------------|---------------|
| Connected air duct size | mm | 125 |
| Speed | - | 1 |
| Minimum supply voltage | V | 220 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50/60 |
| Rated power | W | 24 |
| Unit current | A | 0.105 |
| Maximum airflow | m ³ /h | 226 |
| Sound pressure level LpA at 3 m | dB(A) | 37 |
| Weight | kg | 0.81 |
| Ambient air temperature min | °C | 1 |
| Ambient air temperature max | °C | 40 |
| Ingress protection rating | - | IP34 |





Dimensions

| ØD | B | H | L | L1 |
|-----|-----|-----|-----|------|
| 125 | 176 | 140 | 114 | 12.5 |



Accessories

Flanges

| Name | Photo | Description |
|------------------------|---|--|
| KO 125 |  | Back valve is designed for domestic fan series VENTS M, M1, D, S, M3, X, X1, LD, LD Fresh time, Silenta-M, Silenta-S, Modern, Vitro star, Z star, X star |
| FO 125 |  | The window flange applicable for all VENTS fans except for VKO, VKO1, iFan, Quiet, MAO, CF |

