


125 LD Q



Axial decorative fans for exhaust ventilation

- Maximum airflow: 108
- Sound pressure level LpA at 3 m: 31
- Motor type: AC
- Casing material: Plastic

	Unit of measurement	125 LD Q
Connected air duct size	mm	125
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	9.3
Unit current	A	0.06
Maximum airflow	m ³ /h	108
Sound pressure level LpA at 3 m	dB(A)	31
Weight	kg	0.74
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IP34





Dimensions

$\varnothing D$	B	H	L	L1
125	177	140	135	34




Accessories

Cooker Hoods

Name	Photo	Description
FO_125		The window flange applicable for all VENTS fans except for VKO, VKO1, iFan, Quiet, MAO, CF
KO_125		Back valve is designed for domestic fan series VENTS M, M1, D, S, M3, X, X1, LD, LD Fresh time, Silenta-M, Silenta-S, Modern, Vitro star, Z star, X star

Ecodesign



Trademark	Vents					
Model	125 LD Q					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	30.9	B	14.5	E	5.1	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Single speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	108					
Electric power input (W)	9.3					
Reference flow rate (m ³ /s)	0.021					
Specific power input (SPI) (W/(m ³ /h))	0.086					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	49					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	108		108		108	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3355		1715		776	