

125 Solid T L



Axial decorative fans for extract ventilation with low power consumption

- Maximum airflow: 155
- Sound pressure level LpA at 3 m: 32
- Motor type: AC
- Casing material: Polypropylene/Thermoplastic elastomer
- Backdraft protection: Backdraft damper
- Timer: Turn off timer

| | Unit of measurement | 125 Solid T L |
|---------------------------------|---------------------|---------------|
| Connected air duct size | mm | 125 |
| Speed | - | 1 |
| Minimum supply voltage | V | 220 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 18 |
| Unit current | A | 0.11 |
| Maximum airflow | m ³ /h | 155 |
| Sound pressure level LpA at 3 m | dB(A) | 32 |
| Weight | kg | 0.75 |
| Ambient air temperature min | °C | 1 |
| Ambient air temperature max | °C | 45 |
| Ingress protection rating | - | IP44 |




Dimensions

| Ø D | B | L | L1 |
|------------|----------|----------|-----------|
| 123.5 | 180 | 85 | 38 |



Accessories

Flanges

| Name | Photo | Description |
|------------------------|--|--|
| FO 125 |  | The window flange applicable for all VENTS fans except for VKO, VKO1, iFan, Quiet, MAO, CF |