

150 VK01 turbo



Axial inline fans, for exhaust or supply ventilation

- Maximum airflow: 365
- Sound pressure level LpA at 3 m: 42
- Motor type: AC
- Casing material: Plastic

	Unit of measurement	150 VK01 turbo
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	36
Unit current	A	0.16
Maximum airflow	m ³ /h	365
Sound pressure level LpA at 3 m	dB(A)	42
Weight	kg	0.58
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IPX4
ErP compliance	-	2016
Cold - Specific energy consumption (SEC)	kWh/(m ² /a)	31.6
SEC Class Cold	-	B
Average - Specific energy consumption (SEC)	kWh/(m ² /a)	15.2
SEC Class Average	-	E
Warm - Specific energy consumption (SEC)	kWh/(m ² /a)	5.8
SEC Class Warm	-	F
Unit category	-	RVU

Type of ventilation unit	-	Unidirectional
Type of drive installed	-	Multi-speed
Type of heat recovery system	-	None
Maximum flow rate	m ³ /h	365
Electric power input	W	36
Reference flow rate	m ³ /s	0.071
Specific power input (SPI)	W/(m ³ /h)	0.063
Control typology	-	Manual control
Maximum external leakage rates	%	2.7
Cold - The annual electricity consumption (AEC)	kWh/a	79
Average - The annual electricity consumption (AEC)	kWh/a	79
Warm - Jährlicher Stromverbrauch (JSV)	kWh/a	79
Cold - The annual heating saved (AHS)	kWh/a	3355
The annual heating saved (AHS) Average	kWh/a	1715
The annual heating saved (AHS) Warm	kWh/a	776
Declared typology	-	RVU UVU
Sound power level	dB(A)	62

Dimensions

ØD	Ød	L	L1
150	59	100	28

