


Boost-I 250 EC R




Mixed-flow inline fans in sound-insulated casings with EC-motors

- Maximum airflow: 1750
- Sound pressure level LpA at 3 m: 48
- Sound insulation
- Motor type: EC
- Impeller type: Mixed-flow
- Casing material: Galvanized steel
- Installation in any position
- Cable with mains plug

	Unit of measurement	Boost-I 250 EC R
Connected air duct size	mm	250
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	168
Unit current	A	1.34
Maximum airflow	m ³ /h	1750
rotation speed at 50hz	-	3282
Sound pressure level LpA at 3 m	dB(A)	48
Weight	kg	9.8
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44








Dimensions

$\varnothing D$	$\varnothing D1$	B	L	L1
249	337	389	601	739







Accessories





For round ducts

Name	Photo	Description
SR 250/600		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SR 250/900		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SR 250/1200		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems



For round ducts

Name	Photo	Description
FB 250		Panel filters
FBK 250-4		Pocket filter
FBK 250-5		Pocket filter
FBK 250-7		Pocket filter




Electrical heaters

Name	Photo	Description
NK 250-1,2-1		Duct electric heater
NK 250-2,0-1		Duct electric heater
NK 250-2,4-1		Duct electric heater
NK 250-3,0-1		Duct electric heater

Water heaters

Name	Photo	Description
NKV 250-2		Duct water heaters are designed for heating of supply air in round ventilation systems. They can be also applied in supply or supply and exhaust ventilating units
NKV 250-4		Duct water heaters are designed for heating of supply air in round ventilation systems. They can be also applied in supply or supply and exhaust ventilating units

For round ducts

Name	Photo	Description
KOM 250		Spring-loaded backdraft damper for round ducts
KOMu 250		Spring-loaded backdraft damper for round ducts
KR 250		Air damper for air flow control in round air ducts

Speed controllers

Name	Photo	Description
R-1/010		Speed controller for EC motors