

Boost-I 250 Un



Inline mixed-flow fans in sound- and heat-insulated casing

- Maximum airflow: 1670
- Sound pressure level LpA at 3 m: 45
- Sound insulation
- Motor type: AC
- Control: Speed controller
- Impeller type: Mixed
- Casing material: Galvanized steel
- Installation in any position
- Cable with mains plug
- Temperature sensor: Remote

	Unit of measurement	Boost-I 250 Un		
Connected air duct size	mm	250		
Speed	-	3		
Phases	-	1		
Minimum supply voltage	V	230		
Maximum supply voltage	V	230		
Power supply frequency	Hz	50		
Rated power	W	144	173	188
Unit current	A	0.70	0.81	0.84
Maximum airflow	m ³ /h	1007	1404	1670
rotation speed at 50hz	-	2292	2626	2876
Sound pressure level LpA at 3 m	dB(A)	38	43	45
Weight	kg	9.8		
Transported air temperature (max)	°C	55		
Transported air temperature (min)	°C	-25		
Ambient air temperature min	°C	1		
Ambient air temperature max	°C	40		
Ingress protection rating	-	IPX4		
Ingress protection rating of the drive	-	IP20		




Dimensions

ØD	ØD1	B	L	L1
249	337	389	601	739






Accessories

For round ducts





Name	Photo	Description
SR 250/600		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SR 250/900		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SR 250/1200		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems

For round ducts



Name	Photo	Description
FB 250		Panel filters
FBK 250-4		Pocket filter
FBK 250-5		Pocket filter

FBK 250-7		Pocket filter
---------------------------	---	---------------




Electrical heaters

Name	Photo	Description
NK 250-1,2-1		Duct electric heater
NK 250-2,0-1		Duct electric heater
NK 250-2,4-1		Duct electric heater
NK 250-3,0-1		Duct electric heater

Water heaters

Name	Photo	Description
NKV 250-2		Duct water heaters are designed for heating of supply air in round ventilation systems. They can be also applied in supply or supply and exhaust ventilating units
NKV 250-4		Duct water heaters are designed for heating of supply air in round ventilation systems. They can be also applied in supply or supply and exhaust ventilating units

For round ducts




Name	Photo	Description
KOM 250		Spring-loaded backdraft damper for round ducts
KOMu 250		Spring-loaded backdraft damper for round ducts
KR 250		Air damper for air flow control in round air ducts

Speed control switches

Name	Photo	Description
------	-------	-------------

P3-1-300		Switch
--------------------------	---	--------

Speed controllers

Name	Photo	Description
RS-1.5-PS		Used in ventilation systems for switching on/off and speed control of single-phase fan motors with voltage control
RS-1-400		Speed controller
RS-3.0-T		Applied in ventilation systems for speed switching ON/OFF and speed control of single-phase power-controlled motors