



Boost-I 400 EC



Mixed-flow inline fans in sound-insulated casings with EC-motors


- Maximum airflow: 5415
- Sound pressure level LpA at 3 m: 49
- Sound insulation
- Motor type: EC
- Impeller type: Mixed-flow
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	Boost-I 400 EC
Connected air duct size	mm	400
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	726
Unit current	A	4.8
Maximum airflow	m ³ /h	5415
rotation speed at 50hz	-	2580
Sound pressure level LpA at 3 m	dB(A)	49
Weight	kg	22.8
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44




Dimensions

$\varnothing D$	$\varnothing D1$	B	L	L1
399	460	517	648	785





Accessories

For round ducts

Name	Photo	Description
KR 400		Air dampers for controlling air flow in round air ducts

For round ducts

Name	Photo	Description
SR 400/1200		Silencers made of galvanized steel filled with non-combustible sound-absorbing material
SR 400/900		Silencers made of galvanized steel filled with non-combustible sound-absorbing material

Speed controllers

Name	Photo	Description
R-1/010		Speed controller for EC motors

Ecodesign

Trademark	Vents
Model	Boost-I 400 EC
Type of drive installed	Integrated VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	1.103
Nominal external pressure (Pa)	298
Maximum external leakage rates (%)	2.7
Static efficiency (%)	45.9
Effective electric power input (kW)	0.73
Sound power level (dB(A))	68
Declared typology	NRVU UVU