



Boost-I 400 EC



Mixed-type duct fans with EC motors in casing with noise and heat insulation


- Maximum airflow: 5415
- Sound pressure level LpA at 3 m: 49
- Sound insulation
- Motor type: EC
- Impeller type: Mixed
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	Boost-I 400 EC
Connected air duct size	mm	400
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	726
Unit current	A	4.8
Maximum airflow	m ³ /h	5415
rotation speed at 50hz	-	2580
Sound pressure level LpA at 3 m	dB(A)	49
Weight	kg	22.8
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44




Dimensions

Ø D	Ø D1	B	L	L1
399	460	517	648	785





Accessories

For round ducts

Name	Photo	Description
KR 400		Air damper for air flow control in round air ducts

For round ducts

Name	Photo	Description
SR 400/1200		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SR 400/900		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems

Speed controllers

Name	Photo	Description
R-1/010		Speed controller for EC motors