

Breezy 200-E Smart L1



Single-room high-efficiency HRV units with ceramic heat exchanger, additional air quality sensors and smart control via mobile app

- Power of electrical preheater: 100
- Maximum airflow: 70
- Sound pressure level LpA at 3 m: 45
- Heat recovery efficiency: 85
- Filter: G3
- Motor type: EC
- Preheater: Electric
- Control: Remote Control
- Casing material: Plastic
- Humidity sensor
- CO2 sensor
- VOC sensor
- Temperature sensor: Built-in

	Unit of measurement	Breezy 200-E Smart L1
Connected air duct size	mm	200
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	16
Power of electrical preheater	W	100
Unit current	A	0.63
Maximum airflow	m ³ /h	70
Sound pressure level LpA at 3 m	dB(A)	45
Heat recovery efficiency	%	85
Heat recovery efficiency, max	%	85
Heat exchanger material	-	Copper
Filter	-	G3
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
Maximum wall thickness	mm	1000

Dimensions

D	L	L1
206	1100	1000

