

Enave-T 350 V L A21





Vertical air handling units with a counterflow polystyrene or enthalpy heat exchanger

- Maximum airflow: 410
- Sound pressure level LpA at 3 m: 26
- Heat exchanger type: Counter flow
- Extract filter: Coarse > 60 %
- Supply filter: Coarse > 60 % (option ePM1 60 %)
- Sound insulation
- Motor type: EC
- Enthalpy heat exchanger
- Bypass: Auto
- Reheater: Optional
- Preheater: Optional
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: EPP
- Humidity sensor: Optional
- CO2 sensor: Optional
- VOC sensor: Optional
- PM2.5 sensor: Optional

| | Unit of measurement | Enave-T 350 V L A21 |
|-----------------------------------|---------------------|----------------------------------|
| Connected air duct size | mm | 160 |
| Speed | - | 1 |
| Phases | - | 1 |
| Minimum supply voltage | V | 230 |
| Maximum supply voltage | V | 230 |
| Power supply frequency | Hz | 50/60 |
| Rated power | W | 213 |
| Unit current | A | 1.62 |
| Maximum airflow | m ³ /h | 410 |
| Sound pressure level LpA at 3 m | dB(A) | 26 |
| Heat recovery efficiency, max | % | 83 |
| Heat exchanger type | - | Counter flow |
| Heat exchanger material | - | Enthalpy |
| Weight | kg | 26 |
| Extract filter | - | Coarse > 60 % |
| Supply filter | - | Coarse > 60 % (option ePM1 60 %) |
| Transported air temperature (max) | °C | 40 |
| Transported air temperature (min) | °C | -25 |
| Ambient air temperature min | °C | 1 |
| Ambient air temperature max | °C | 40 |
| Ambient air humidity max | % | 60 |


| | | |
|--|---|------|
| Ingress protection rating | - | IP22 |
| Ingress protection rating of the drive | - | IP44 |







Dimensions

| Ø D | H | H1 | L | L1 | W | W1 |
|------------|----------|-----------|----------|-----------|----------|-----------|
| 160 | 880 | 939 | 616 | 230 | 770 | 355 |






Accessories






Other accessories

| Name | Photo | Description |
|-----------------------------|---|-----------------|
| SF 496x150x60 Coarse 90% G4 |  | Panel filter G4 |
| SF 496x150x60 ePM1 65% F7 |  | F7 panel filter |

Control Panels for AHU

| Name | Photo | Description |
|--------------------------|---|--|
| A25 |  | Touch screen control panel for controlling industrial and residential air handling units |
| A22 |  | Control panels for controlling industrial and residential air handling units |
| A22 WiFi |  | Control panels for controlling industrial and residential air handling units |

Sensors




| Name | Photo | Description |
|-----------------------|---|-------------------------------|
| HV2 |  | Humidity sensor |
| CO2-3 |  | CO2 sensor |
| CO2-1 |  | CO2 sensors |
| CO2-2 |  | CO2 sensors |
| HR-S |  | Electro-mechanical humidistat |

Electrical heaters


| Name | Photo | Description |
|------|-------|-------------|
|------|-------|-------------|

| | | |
|---------------------------------------|---|--|
| NKP 160-0,8-1 A21 V.2 |  | Inline heaters for heat exchanger frost protection |
| NKP 160-1,2-1 A21 V.2 |  | Inline heaters for heat exchanger frost protection |
| NKP 160-1,7-1 A21 V.2 |  | Inline heaters for heat exchanger frost protection |
| NKP 160-2,0-1 A21 V.2 |  | Inline heaters for heat exchanger frost protection |
| NKD 160-0,8-1 A21 V.2 |  | Inline supply air reheaters with external control |
| NKD 160-1,2-1 A21 V.2 |  | Inline supply air reheaters with external control |
| NKD 160-1,7-1 A21 V.2 |  | Inline supply air reheaters with external control |
| NKD 160-2,0-1 A21 V.2 |  | Inline supply air reheaters with external control |

For round ducts

| Name | Photo | Description |
|-----------------------------|---|---|
| SR 160/600 |  | Silencers made of galvanized steel filled with non-combustible sound-absorbing material |
| SR 160/900 |  | Silencers made of galvanized steel filled with non-combustible sound-absorbing material |
| SR 160/1200 |  | Silencers made of galvanized steel filled with non-combustible sound-absorbing material |

For round ducts

| Name | Photo | Description |
|-------------------------|---|---|
| KRV 160 |  | Air dampers for automatic air flow control in round ducts |

Electric actuators


| Name | Photo | Description |
|------|-------|-------------|
|------|-------|-------------|

[Belimo TF230](#)



The actuators are designed for controlling air dampers with cross section up to 0.4 m² performing protection functions

Ecodesign



| | | | | | | |
|---|----------------------|----|---------|---|------|---|
| Trademark | Vents | | | | | |
| Model | Enave-T 350 V L A21 | | | | | |
| Specific energy consumption (SEC) (kWh/(m ² /a)) | Cold | | Average | | Warm | |
| | 78.9 | A+ | 41.2 | A | 16.9 | E |
| Type of ventilation unit | Bidirectional | | | | | |
| Type of drive installed | Variable speed | | | | | |
| Type of heat recovery system | Recuperative | | | | | |
| Thermal efficiency of heat recovery (%) | 81 | | | | | |
| Maximum flow rate (m ³ /h) | 360 | | | | | |
| Electric power input (W) | 213 | | | | | |
| Reference flow rate (m ³ /s) | 0.071 | | | | | |
| Reference pressure difference (Pa) | 50 | | | | | |
| Specific power input (SPI) (W/(m ³ /h)) | 0.26 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates (%) | 2.7 | | | | | |
| Maximum external leakage rates (%) | 2.7 | | | | | |
| Declared typology | RVU BVU | | | | | |
| Sound power level (dB(A)) | 46 | | | | | |
| The annual electricity consumption (AEC) (kWh/a) | Cold | | Average | | Warm | |
| | 720 | | 183 | | 138 | |
| The annual heating saved (AHS) (kWh/a) | Cold | | Average | | Warm | |
| | 8817 | | 4507 | | 2038 | |