

KSB 100



Inline centrifugal fans in heat- and sound-insulated casing

- Maximum airflow: 240
- Sound pressure level LpA at 3 m: 33
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	KSB 100	
Connected air duct size	mm	100	
Speed	-	1	
Minimum supply voltage	V	220	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50/60	
Rated power	W	73	
Unit current	A	0.32	
Maximum airflow	m ³ /h	240	
Sound pressure level LpA at 3 m	dB(A)	33	
Weight	kg	5.4	
Transported air temperature (max)	°C	55	
Transported air temperature (min)	°C	-25	
Ingress protection rating	-	IPX4	
ErP compliance	-	2016	2018
Cold - Specific energy consumption (SEC)	kWh/(m ³ /a)	50.1	
SEC Class Cold	-	A+	
Average - Specific energy consumption (SEC)	kWh/(m ³ /a)	23.1	
SEC Class Average	-	C	
Warm - Specific energy consumption (SEC)	kWh/(m ³ /a)	7.6	
SEC Class Warm	-	F	
Unit category	-	RVU	

Type of ventilation unit	-	Unidirectional
Type of drive installed	-	Multi-speed
Type of heat recovery system	-	None
Maximum flow rate	m ³ /h	205
Electric power input	W	73
Reference flow rate	m ³ /s	0.04
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m ³ /h)	0.28
Control typology	-	Local demand control
Maximum external leakage rates	%	2.7
Internet address	-	https://www.ventilation-system.com
Contact name	-	Export
Address	-	1, ul. Mikh. Kotzubinskogo, 01030 Kyiv, Ukraine
Phone number	-	(+38) 044 406 36 25
Email address	-	export@vents.ua
Cold - The annual electricity consumption (AEC)	kWh/a	209
Average - The annual electricity consumption (AEC)	kWh/a	209
Warm - Jährlicher Stromverbrauch (JSV)	kWh/a	209
Cold - The annual heating saved (AHS)	kWh/a	5536
The annual heating saved (AHS) Average	kWh/a	2830
The annual heating saved (AHS) Warm	kWh/a	1280
Declared typology	-	RVU BVU
Sound power level	dB(A)	33

Dimensions

ØD	B	B1	H	L	L1	L2
99	322	280	192	447	380	350

