



KSB 125 K2 S



Inline centrifugal fans in heat- and sound-insulated casing


- Maximum airflow: 484
- Sound pressure level LpA at 3 m: 40
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position

	Unit of measurement	KSB 125 K2 S
Connected air duct size	mm	125
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	88
Unit current	A	0.37
Maximum airflow	m³/h	484
rotation speed at 50hz	-	2670
Sound pressure level LpA at 3 m	dB(A)	40
Weight	kg	19
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44




Dimensions

ØD	B	B1	H	L	L1	L2
124	533	333	280	630	617	525



Ecodesign



Trademark	Vents		
Model	KSB 125 K2 S		
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold	Average	Warm
	-51.4	A+	-24.4 C -8.9 F
Type of ventilation unit	Unidirectional		
Type of drive installed	Variable speed		
Type of heat recovery system	None		
Maximum flow rate (m ³ /h)	420		
Electric power input (W)	88		
Reference flow rate (m ³ /s)	0.082		
Reference pressure difference (Pa)	50		
Specific power input (SPI) (W/(m ³ /h))	0.296		
Control typology	Local demand control		
Maximum external leakage rates (%)	2.7		
Declared typology	RVU UVU		
Sound power level (dB(A))	60		
The annual electricity consumption (AEC) (kWh/a)	Cold	Average	Warm
	157	157	157
The annual heating saved (AHS) (kWh/a)	Cold	Average	Warm
	5536	2830	1280