

# KSB 200 K2



Inline centrifugal fans in heat- and sound-insulated casing

- Maximum airflow: 770
- Sound pressure level LpA at 3 m: 42
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Aluzinc
- Installation in any position

	Unit of measurement	KSB 200 K2
Connected air duct size	mm	200
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	164
Unit current	A	0.71
Maximum airflow	m <sup>3</sup> /h	770
rotation speed at 50hz	-	2580
Sound pressure level LpA at 3 m	dB(A)	42
Weight	kg	22.6
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44
ErP compliance	-	2016, 2018
Cold - Specific energy consumption (SEC)	kWh/(m <sup>2</sup> /a)	50.9
SEC Class Cold	-	A+
Average - Specific energy consumption (SEC)	kWh/(m <sup>2</sup> /a)	23.8
SEC Class Average	-	C

Warm - Specific energy consumption (SEC)	kWh/(m <sup>2</sup> /a)	8.3
SEC Class Warm	-	F
Unit category	-	RVU
Type of ventilation unit	-	Unidirectional
Type of drive installed	-	Variable speed
Type of heat recovery system	-	None
Maximum flow rate	m <sup>3</sup> /h	690
Electric power input	W	152
Reference flow rate	m <sup>3</sup> /s	0.134
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m <sup>3</sup> /h)	0.34
Control typology	-	Local demand control
Maximum external leakage rates	%	2.7
Cold - The annual electricity consumption (AEC)	kWh/a	180
Average - The annual electricity consumption (AEC)	kWh/a	180
Warm - Jährlicher Stromverbrauch (JSV)	kWh/a	180
Cold - The annual heating saved (AHS)	kWh/a	5536
The annual heating saved (AHS) Average	kWh/a	2830
The annual heating saved (AHS) Warm	kWh/a	1280
Declared typology	-	RVU UVU
Sound power level	dB(A)	62

## Dimensions

ØD	B	B1	H	L	L1	L2
198	535	357.5	355	632	628	535

