



KSB 250 EC



Centrifugal inline fans in insulated casing


- Maximum airflow: 1145
- Sound pressure level LpA at 3 m: 40
- Sound insulation
- Motor type: EC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	KSB 250 EC
Connected air duct size	mm	250
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	163.7
Unit current	A	1.34
Maximum airflow	m³/h	1145
Sound pressure level LpA at 3 m	dB(A)	40
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP55




Dimensions

ØD	L	B	H	L1	B1	L2	B2
249	435	485	295	490	590	368	506



Ecodesign



Trademark	Vents			
Model	KSB 250 EC			
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average	Warm
	-53.9	A+	-26.8	B -11.3 E
Type of ventilation unit	Unidirectional			
Type of drive installed	Variable speed			
Type of heat recovery system	None			
Maximum flow rate (m ³ /h)	980			
Electric power input (W)	163.5			
Reference flow rate (m ³ /s)	0.191			
Reference pressure difference (Pa)	50			
Specific power input (SPI) (W/(m ³ /h))	0.114			
Control typology	Local demand control			
Maximum external leakage rates (%)	2.7			
Declared typology	RVU UVU			
The annual electricity consumption (AEC) (kWh/a)	Cold		Average	Warm
	60	60	60	
The annual heating saved (AHS) (kWh/a)	Cold		Average	Warm
	5536	2830	1280	