


# KSV 100 G4/F8



Centrifugal fans in sound-insulated casing

- Maximum airflow: 180
- Sound pressure level LpA at 3 m: 23
- Filter: G4+F8
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	KSV 100 G4/F8
Connected air duct size	mm	100
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	53
Unit current	A	0.27
Maximum airflow	m <sup>3</sup> /h	180
Sound pressure level LpA at 3 m	dB(A)	23
Weight	kg	14.16
Filter	-	G4+F8
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44




**Dimensions**

D	L	H	B	L1	B1	L2	B2
100	705	250	415	805	508	650	458



## Ecodesign



Trademark	Vents					
Model	KSV 100 G4/F8					
Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a))	Cold		Average		Warm	
	-49.7	A+	-22.6	D	-7.1	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m <sup>3</sup> /h)	116					
Electric power input (W)	50					
Reference flow rate (m <sup>3</sup> /s)	0.023					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m <sup>3</sup> /h))	0.431					
Control typology	Local demand control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	43					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	228		228		228	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	5536		2830		1280	