

KSV 150




Centrifugal fans in sound-insulated casing

- Maximum airflow: 440
- Sound pressure level LpA at 3 m: 27
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Coated steel
- Installation in any position


	Unit of measurement	KSV 150
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	107
Unit current	A	0.49
Maximum airflow	m³/h	440
Sound pressure level LpA at 3 m	dB(A)	27
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44

Dimensions

D	L	H	B	L1	B1	L2	B2
150	735	300	440	835	533	680	483



Ecodesign



Trademark	Vents		
Model	KSV 150		
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold -52.3	Average A+	Warm -25.3 C -9.8 F
Type of ventilation unit	Unidirectional		
Type of drive installed	Multi-speed		
Type of heat recovery system	None		
Maximum flow rate (m ³ /h)	450		
Electric power input (W)	103		
Reference flow rate (m ³ /s)	0.088		
Reference pressure difference (Pa)	50		
Specific power input (SPI) (W/(m ³ /h))	0.229		
Control typology	Local demand control		
Maximum external leakage rates (%)	2.7		
Declared typology	RVU UVU		
Sound power level (dB(A))	47		
The annual electricity consumption (AEC) (kWh/a)	Cold 121	Average 121	Warm 121
The annual heating saved (AHS) (kWh/a)	Cold 5536	Average 2830	Warm 1280