

KSV 150 Duo G4/H13/Carbon



Centrifugal fans in sound-insulated casing

- Maximum airflow: 355
- Sound pressure level LpA at 3 m: 27
- Filter: G4+H13+Carbon
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Coated steel
- Installation in any position

| | Unit of measurement | KSV 150 Duo G4/H13/Carbon | |
|--|---------------------|---------------------------|------|
| Connected air duct size | mm | 150 | |
| Speed | - | 2 | |
| Minimum supply voltage | V | 230 | |
| Maximum supply voltage | V | 230 | |
| Power supply frequency | Hz | 50 | |
| Rated power | W | 85 | 114 |
| Unit current | A | 0.38 | 0.54 |
| Maximum airflow | m ³ /h | 280 | 355 |
| Sound pressure level LpA at 3 m | dB(A) | 16 | 27 |
| Weight | kg | 17.08 | |
| Filter | - | G4+H13+Carbon | |
| Transported air temperature (max) | °C | 40 | |
| Transported air temperature (min) | °C | -25 | |
| Ingress protection rating | - | IPX4 | |
| Ingress protection rating of the drive | - | IP44 | |

Dimensions

| D | L | H | B | L1 | B1 | L2 | B2 |
|-----|-----|-----|-----|-----|-----|-----|-----|
| 150 | 735 | 300 | 440 | 835 | 533 | 680 | 483 |

