


KSV 150 G4/F8



Centrifugal inline fans with forward curved blades in sound-insulated casings with filters


- Maximum airflow: 400
- Sound pressure level LpA at 3 m: 27
- Filter: G4+F8
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position

	Unit of measurement	KSV 150 G4/F8
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	104
Unit current	A	0.48
Maximum airflow	m ³ /h	400
Sound pressure level LpA at 3 m	dB(A)	27
Weight	kg	16.17
Filter	-	G4+F8
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44




Dimensions

D	L	H	B	L1	B1	L2	B2
150	735	300	440	835	533	680	483



Ecodesign



Trademark	Vents					
Model	KSV 150 G4/F8					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-50.2	A+	-23.1	C	-7.6	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	246					
Electric power input (W)	96					
Reference flow rate (m ³ /s)	0.048					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m ³ /h))	0.39					
Control typology	Local demand control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	47					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	207		207		207	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	5536		2830		1280	