


# KSV 150 Q G4/F8



Centrifugal fans in sound-insulated casing


- Maximum airflow: 330
- Sound pressure level LpA at 3 m: 25
- Filter: G4+F8
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Coated steel
- Installation in any position

	<b>Unit of measurement</b>	<b>KSV 150 Q G4/F8</b>
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	61
Unit current	A	0.25
Maximum airflow	m³/h	330
Sound pressure level LpA at 3 m	dB(A)	25
Weight	kg	14.17
Filter	-	G4+F8
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44




## Dimensions

D	L	H	B	L1	B1	L2	B2
150	705	250	415	805	508	650	458



## Ecodesign



Trademark	Vents		
Model	KSV 150 Q G4/F8		
Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a))	Cold	Average	Warm
	-52.3	A+	-25.2 C -9.7 F
Type of ventilation unit	Unidirectional		
Type of drive installed	Multi-speed		
Type of heat recovery system	None		
Maximum flow rate (m <sup>3</sup> /h)	242		
Electric power input (W)	56		
Reference flow rate (m <sup>3</sup> /s)	0.047		
Reference pressure difference (Pa)	50		
Specific power input (SPI) (W/(m <sup>3</sup> /h))	0.231		
Control typology	Local demand control		
Maximum external leakage rates (%)	2.7		
Declared typology	RVU UVU		
Sound power level (dB(A))	45		
The annual electricity consumption (AEC) (kWh/a)	Cold	Average	Warm
	122	122	122
The annual heating saved (AHS) (kWh/a)	Cold	Average	Warm
	5536	2830	1280