



MPA 1000 E-6.0 EC A31



Air supply units in the sound- and heat-insulated casing


- Power of electrical reheater: 6000
- Maximum airflow: 1000
- Sound pressure level LpA at 3 m: 45
- Filter: Coarse 90% / G4 (option ePM1 70% / F7)
- Sound insulation
- Motor type: EC
- Reheater: Electric
- BMS protocol: ModBus
- Control: Wired control panel
- Casing material: Aluzinc steel

	Unit of measurement	MPA 1000 E-6.0 EC A31
Connected air duct size	mm	400x200
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	165
Power of electrical reheater	W	6000
Unit current	A	11
Maximum airflow	m ³ /h	1000
Sound pressure level LpA at 3 m	dB(A)	45
Weight	kg	30
Filter	-	Coarse 90% / G4 (option ePM1 70% / F7)
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP44





Dimensions

H	H1	L	L1	W	W1	W2	W3
380	200	900	770	600	653	746	400




Accessories

Other accessories

Name	Photo	Description
SF 536x316x48 G4		Panel filter G4
SF 536x316x48 F7		F7 panel filter

For rectangular ducts

Name	Photo	Description
VVG 400x200		Flexible anti-vibration inserts for round air ducts

For rectangular ducts



Name	Photo	Description
SR 400x200		Plate silencer for installation in rectangular ducts

Airflow regulators

Name	Photo	Description
------	-------	-------------

RRV 400x200		Air flow controllers
-----------------------------	---	----------------------

Electric actuators

Name	Photo	Description
Belimo TF230		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions
Belimo TF24		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions