




MPA 2000 W EC A31

Air supply units in the sound- and heat-insulated casing




- Maximum airflow: 2150
- Sound pressure level LpA at 3 m: 53
- Filter: Coarse 90% / G4 (option ePM1 70% / F7)
- Sound insulation
- Motor type: EC
- Reheater: Water
- BMS protocol: ModBus
- Control: Wired control panel
- Casing material: Aluzinc steel

	Unit of measurement	MPA 2000 W EC A31
Connected air duct size	mm	500x300
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	387
Unit current	A	1.7
Maximum airflow	m ³ /h	2150
Sound pressure level LpA at 3 m	dB(A)	53
Weight	kg	45
Filter	-	Coarse 90% / G4 (option ePM1 70% / F7)
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP44





Dimensions

H	H1	H2	L	L1	L2	W	W1	W2	W3
440	300	318	900	770	65	700	754	847	500




Accessories

Other accessories

Name	Photo	Description
SF 636x376x48 G4		Panel filter G4
SF 636x376x48 F7		F7 panel filter

For rectangular ducts

Name	Photo	Description
VVG 500x300		Flexible anti-vibration inserts for round air ducts



For rectangular ducts

Name	Photo	Description
SR 500x300		Plate silencer for installation in rectangular ducts

Airflow regulators

Name	Photo	Description
RRV 500x300		Air flow controllers

Electric actuators

Name	Photo	Description
Belimo TF230		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions
Belimo TF24		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions