



MPA 4000 W EC A31



Air supply units in the sound- and heat-insulated casing


- Maximum airflow: 4950
- Sound pressure level LpA at 3 m: 54
- Filter: Coarse 90% / G4 (option ePM1 70% / F7)
- Sound insulation
- Motor type: EC
- Reheater: Water
- BMS protocol: ModBus
- Control: Wired control panel
- Casing material: Aluzinc steel

	Unit of measurement	MPA 4000 W EC A31
Connected air duct size	mm	700x400
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	698
Unit current	A	1.06
Maximum airflow	m ³ /h	4950
Sound pressure level LpA at 3 m	dB(A)	54
Weight	kg	58
Filter	-	Coarse 90% / G4 (option ePM1 70% / F7)
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP44





Dimensions

H	H1	H2	L	L1	L2	W	W1	W2	W3
550	400	380	1200	1070	65	940	993	1087	700



Accessories


Other accessories

Name	Photo	Description
SF 874x485x80 G4		Panel filter G4
SF 874x485x80 F7		F7 panel filter

For rectangular ducts

Name	Photo	Description
VVG 700x400		Flexible anti-vibration connector



For rectangular ducts

Name	Photo	Description
SR 700x400		The plate silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems

Airflow regulators

Name	Photo	Description
RRV 700x400		Air flow controllers

Electric actuators

Name	Photo	Description
Belimo TF230		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions
Belimo TF24		The actuators are designed for controlling air dampers with cross section up to 0.4 m ² performing protection functions