


OV 4E 350




Low pressure axial fans in the steel casing for wall mounting

- Maximum airflow: 2500
- Sound pressure level LpA at 3 m: 46
- Motor type: AC
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position


	Unit of measurement	OV 4E 350
Connected air duct size	mm	350
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	140
Unit current	A	0.65
Maximum airflow	m ³ /h	2500
Sound pressure level LpA at 3 m	dB(A)	46
Weight	kg	7.8
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP24





Dimensions

∅D	∅d	B	B1	L
374	9	485	435	165



Ecodesign

Trademark	Vents
Model	OV 4E 350
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	0.477
Nominal external pressure (Pa)	80
Maximum external leakage rates (%)	2.7
Static efficiency (%)	29.9
Declared typology	NRVU UVU
Sound power level (dB(A))	82
Effective electric power input (kW)	0.13