

# OV 4E 350



Low pressure axial fans in the steel casing for wall mounting

- Maximum airflow: 2500
- Sound pressure level LpA at 3 m: 46
- Motor type: AC
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	OV 4E 350
Connected air duct size	mm	350
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	140
Unit current	A	0.65
Maximum airflow	m <sup>3</sup> /h	2500
Sound pressure level LpA at 3 m	dB(A)	46
Weight	kg	7.8
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP24
ErP compliance	-	N/A
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m <sup>3</sup> /s	0.477
Nominal external pressure	Pa	80
Maximum external leakage rates	%	2.7
Static efficiency	%	29.9

Declared typology	-	NRVU UVU
Sound power level	dB(A)	82
Effective electric power input	kW	0.13

## Dimensions

$\varnothing D$	$\varnothing d$	B	B1	L
374	9	485	435	165

