

# OVK 2E 300



Low pressure axial fans in the steel casing for wall mounting

- Maximum airflow: 2230
- Sound pressure level LpA at 3 m: 53
- Motor type: AC
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	OVK 2E 300
Connected air duct size	mm	300
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	145
Unit current	A	0.66
Maximum airflow	m <sup>3</sup> /h	2230
Sound pressure level LpA at 3 m	dB(A)	53
Weight	kg	5.9
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP24
ErP compliance	-	N/A
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m <sup>3</sup> /s	0.383
Nominal external pressure	Pa	110
Maximum external leakage rates	%	2.7
Static efficiency	%	30.5

Declared typology	-	NRVU UVU
Sound power level	dB(A)	80
Effective electric power input	kW	0.141

## Dimensions

$\varnothing D$	$\varnothing D1$	$\varnothing D2$	$\varnothing d$	L
317	380	397	9	145

