
OVK 2E 300




Wall-mounted axial fans

- Sound pressure level LpA at 3 m: 53
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position


	Unit of measurement	OVK 2E 300	
Connected air duct size	mm	300	
Phases	-	1	
Maximum supply voltage	V	240	
Minimum supply voltage	V	220	
Power supply frequency	Hz	50	60
Rated power	W	145	
Unit current	A	0.66	
Maximum airflow	m³/h	2230	
Rotation speed at 50hz	-	2300	
Sound pressure level LpA at 3 m	dB(A)	53	
Weight	kg	5.9	
Transported air temperature (max)	°C	60	
Transported air temperature (min)	°C	-30	
Ingress protection rating	-	IP24	
Ingress protection rating of the drive	-	IP54	
Impeller material	-	Coated steel	


speed_1_50Hz
speed_1_60Hz
150
100
50
0
Static pressure [Pa]
0
1,000
2,000
Airflow [m3/h]



Dimensions

ØD	ØD1	ØD2	Ød	L
317	380	397	9	145


L
ød
ØD
ØD1
ØD2

Ecodesign

Trademark	Vents
Model	OVK 2E 300
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal external pressure (Pa)	110
Maximum external leakage rates (%)	2.7
Static efficiency (%)	30.5
Sound power level (dB(A))	80
Effective electric power input (kW)	0.141
Declared typology	NRVU UVU