

OVK1 150



Low pressure axial fans in the steel casing for wall mounting

- Maximum airflow: 200
- Sound pressure level LpA at 3 m: 33
- Motor type: AC
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	OVK1 150
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	36
Unit current	A	0.26
Maximum airflow	m ³ /h	200
Sound pressure level LpA at 3 m	dB(A)	33
Weight	kg	2.5
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP24
Ingress protection rating of the drive	-	IP44
ErP compliance	-	N/A
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m ³ /s	0.027
Nominal external pressure	Pa	27
Maximum external leakage rates	%	2.7

Static efficiency	%	2.8
Declared typology	-	NRVU UVU
Sound power level	dB(A)	53
Effective electric power input	kW	0.027

Dimensions

$\varnothing D$	$\varnothing D1$	$\varnothing D2$	$\varnothing d$	L
162	190	220	7	120

