


PA 02 E LCD



Suspended air supply units in the sound- and heat-insulated casing with the water or electric heater


- Power of electrical reheater: 18000
- Maximum airflow: 2500
- Sound pressure level LpA at 3 m: 54
- Filter: G4
- Sound insulation
- Motor type: AC
- Reheater: Electric
- Control: Remote Control
- Casing material: Galvanized steel

	Unit of measurement	PA 02 E LCD
Connected air duct size	mm	500x300
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	620
Power of electrical reheater	W	18000
Unit current	A	27.1
Maximum airflow	m ³ /h	2500
Sound pressure level LpA at 3 m	dB(A)	54
Weight	kg	61
Filter	-	G4
Transported air temperature (max)	°C	45
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	-25
Ambient air temperature max	°C	45
Ambient air humidity max	%	80
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP44



Dimensions

B	B1	B2	B3	H	H1	H2	L	L1
500	520	689	646	300	320	447	1250	1212



Accessories


For rectangular ducts

Name	Photo	Description
SR 500x300		The plate silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems

Airflow regulators

Name	Photo	Description
RRV 500x300		Air flow controllers


Mixing chambers

Name	Photo	Description
SKRA 500x300/24		The mixing chambers is designed for mixing (recirculation) of extract and intake air in a required ratio


For rectangular ducts

Name	Photo	Description
VVG 500x300		Flexible anti-vibration connector

Water coolers

Name	Photo	Description
OKW 500x300-3		Duct water coil air coolers are designed for cooling of supply air in rectangular ventilation systems and can be applied in supply or supply and exhaust ventilation systems

Freon coolers

Name	Photo	Description
OKF 500x300-3		Direct-expansion duct coolers are designed for cooling of supply air in rectangular ventilation systems and can be used either for supply or supply and exhaust units

Other accessories

Name	Photo	Description
------	-------	-------------

SF 540x340x48 G4



Panel filter G4