
# PA 03 W4 LCD



Suspended air supply units in the sound- and heat-insulated casing with the water or electric heater


- Sound pressure level LpA at 3 m: 57
- Filter: G4 (F7 option)
- Sound-insulated casing
- Reheater: Water
- Control: Remote Control
- Casing material: Galvanized steel

| | Unit of measurement | PA 03 W4 LCD |
|---|---|---|
| Connected air duct size | mm | 600x350 |
| Phases | - | 3 |
| Minimum supply voltage | V | 400 |
| Maximum supply voltage | V | 400 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 1330 |
| Unit current | A | 2.4 |
| Maximum airflow | m³/h | 3260 |
| Rotation speed at 50hz | - | 2730 |
| Sound pressure level LpA at 3 m | dB(A) | 57 |
| Weight | kg | 94 |
| Filter | - | G4 (F7 option) |
| Transported air temperature (max) | °C | 45 |
| Transported air temperature (min) | °C | -25 |
| Ambient air temperature min | °C | -25 |
| Ambient air temperature max | °C | 45 |
| Ingress protection rating | - | IP22 |
| Ambient air humidity max | % | 80 |
| Ingress protection rating of the drive | - | IP44 |





## Dimensions

| B | B1 | B2 | B3 | H | H1 | H2 | L | L1 |
|---|---|---|---|---|---|---|---|---|
| 600 | 620 | 787 | 744 | 350 | 370 | 500 | 1252 | 1212 |




## Accessories

### For rectangular ducts

| Name | Photo | Description |
|---|---|---|
| SR 600x350 |  | Plate silencer for installation in rectangular ducts |

### For rectangular ducts

| Name | Photo | Description |
|---|---|---|
| VVG 600x350 |  | Flexible anti-vibration inserts for round air ducts |

### Mixing chambers

| Name | Photo | Description |
|---|---|---|
| SKRA 600x350/24 |  | Mixing chambers for mixing (recirculating) part of the exhaust air with the outdoor air in the appropriate proportion |

### Mixing chambers

| Name | Photo | Description |
|---|---|---|
| USWK 3/4-4 |  | The mixing unit USWK is designed for smooth heat medium flow control in ventilation systems equipped with water heaters or coolers for supply air temperature regulation |
| USWK 3/4-6 |  | The mixing unit USWK is designed for smooth heat medium flow control in ventilation systems equipped with water heaters or coolers for supply air temperature regulation |

### Airflow regulators

| Name | Photo | Description |
|---|---|---|
| RRV 600x350 |  | Air flow controllers |

### Water coolers

| Name | Photo | Description |
|---|---|---|
| OKW 600x350-3 |  | Rectangular inline water coolers |

### Freon coolers

| Name | Photo | Description |
|---|---|---|
| OKF 600x350-3 |  | Rectangular inline direct evaporative coolers |

### Other accessories

| Name | Photo | Description |
|---|---|---|
| SFK 637x395x27 F7 |  | F7 pocket filter |
| SFK 637x395x27 G4 |  | G4 pocket filter |