

Quietline 125 Duo



Extra quiet axial inline fans with low power consumption

- Maximum airflow: 197
- Sound pressure level LpA at 3 m: 32
- Motor type: AC
- Casing material: Polypropylene/Thermoplastic elastomer
- Backdraft protection: Backdraft damper


	Unit of measurement	Quietline 125 Duo	
Connected air duct size	mm	125	
Speed	-	2	
Minimum supply voltage	V	220	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50	
Rated power	W	10	13
Unit current	A	0.065	0.085
Maximum airflow	m ³ /h	145	197
Sound pressure level LpA at 3 m	dB(A)	29	32
Weight	kg	0.75	
Ambient air temperature min	°C	1	
Ambient air temperature max	°C	40	
Ingress protection rating	-	IPX4	

Dimensions

L	ØD	k
161.5	125	-



Ecodesign



Trademark	Vents					
Model	Quietline 125 Duo					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-31.4	B	-15	E	-5.6	F
Type of ventilation unit	Unidirectional					
Type of drive installed	2-speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	197					
Electric power input (W)	13					
Reference flow rate (m ³ /s)	0.04					
Specific power input (SPI) (W/(m ³ /h))	0.069					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	49					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	86		86		86	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3355		1715		776	