

# Quietline 150 Extra




Extra quiet axial inline fans with low power consumption

- Maximum airflow: 375
- Sound pressure level LpA at 3 m: 41
- Motor type: AC
- Casing material: Polypropylene/Thermoplastic elastomer
- Backdraft protection: Backdraft damper


	Unit of measurement	Quietline 150 Extra	
Connected air duct size	mm	150	
Speed	-	2	
Minimum supply voltage	V	220	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50	
Rated power	W	22	25
Unit current	A	0.103	0.109
Maximum airflow	m <sup>3</sup> /h	285	375
Sound pressure level LpA at 3 m	dB(A)	36	41
Weight	kg	1.3	
Ambient air temperature min	°C	1	
Ambient air temperature max	°C	40	
Ingress protection rating	-	IPX4	

## Dimensions

L	ØD	k
182	150	-



## Ecodesign



Trademark	Vents					
Model	Quietline 150 Extra					
Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a))	Cold		Average		Warm	
	-31.1	B	-14.7	E	-5.3	F
Type of ventilation unit	Unidirectional					
Type of drive installed	2-speed					
Type of heat recovery system	None					
Maximum flow rate (m <sup>3</sup> /h)	375					
Electric power input (W)	25					
Reference flow rate (m <sup>3</sup> /s)	0.079					
Specific power input (SPI) (W/(m <sup>3</sup> /h))	0.077					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	56					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	97		97		97	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3355		1715		776	