

# Solo RA1-60-9 R V.2



The Solo ventilator is the most suitable solution for utility rooms, closets, and cloakrooms. Low power consumption will save electricity by providing clean and fresh air to any room with area of up to 25 m<sup>2</sup>. The area is approximate and depends on the ventilation standards in your country and the model of the ventilator

- Air flow in heat recovery mode: 30
- Sound pressure level LpA at 3 m: 29
- Sound pressure level LpA at 1 m: 38
- Heat recovery efficiency: 85
- Filter: G3
- Motor type: EC
- Control: Remote Control
- Casing material: Plastic
- Humidity sensor

	Unit of measurement	Solo RA1-60-9 R V.2	
Speed	-	2	
Minimum supply voltage	V	220	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50/60	
Rated power	W	1.10	3.20
Unit current	A	0.021	0.042
Air flow in ventilation mode	m <sup>3</sup> /h	35	60
Air flow in heat recovery mode	m <sup>3</sup> /h	18	30
Sound pressure level LpA at 3 m	dB(A)	27	29
Sound pressure level LpA at 1 m	dB(A)	27	38
Heat recovery efficiency	%	85	
Heat recovery efficiency, max	%	85	
Filter	-	G3	
Transported air temperature (max)	°C	40	
Transported air temperature (min)	°C	-15	
Ambient air temperature min	°C	1	
Ambient air temperature max	°C	40	
Ambient air humidity max	%	65	
Ingress protection rating	-	IP24	

## Dimensions

ØD	B	B1	L	L1	L2
156	205	186	305-380	35	86

