

TT PRO 125



Inline mixed-flow fans

- Maximum airflow: 350
- Sound pressure level LpA at 3 m: 34
- Motor type: AC
- Impeller type: Mixed
- Casing material: Plastic
- Installation in any position

	Unit of measurement	TT PRO 125	
Connected air duct size	mm	125	
Speed	-	2	
Minimum supply voltage	V	230	
Maximum supply voltage	V	230	
Power supply frequency	Hz	50/60	
Rated power	W	25	29
Unit current	A	0.11	0.13
Maximum airflow	m³/h	240	350
Sound pressure level LpA at 3 m	dB(A)	29	34
Weight	kg	2.15	
Transported air temperature (max)	°C	60	
Ingress protection rating	-	IPX4	
Ingress protection rating of the drive	-	IPX4	
ErP compliance	-	2016, 2018	
Cold - Specific energy consumption (SEC)	kWh/(m²/a)	53.6	
SEC Class Cold	-	A+	
Average - Specific energy consumption (SEC)	kWh/(m²/a)	26.6	
SEC Class Average	-	B	
Warm - Specific energy consumption (SEC)	kWh/(m²/a)	11.1	
SEC Class Warm	-	E	
Unit category	-	RVU	

Type of ventilation unit	-	Unidirectional
Type of drive installed	-	Variable speed
Type of heat recovery system	-	None
Maximum flow rate	m ³ /h	275
Electric power input	W	29
Reference flow rate	m ³ /s	0.053
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m ³ /h)	0.13
Control typology	-	Local demand control
Maximum external leakage rates	%	2.7
Cold - The annual electricity consumption (AEC)	kWh/a	69
Average - The annual electricity consumption (AEC)	kWh/a	69
Warm - Jährlicher Stromverbrauch (JSV)	kWh/a	69
Cold - The annual heating saved (AHS)	kWh/a	5536
The annual heating saved (AHS) Average	kWh/a	2830
The annual heating saved (AHS) Warm	kWh/a	1280
Declared typology	-	RVU UVU
Sound power level	dB(A)	54

Dimensions

ØD	B	H	L
123	195.6	226	258.5

