

TT PRO 250



Inline mixed-flow fans

- Maximum airflow: 1400
- Sound pressure level LpA at 3 m: 51
- Motor type: AC
- Impeller type: Mixed
- Casing material: Plastic
- Installation in any position

	Unit of measurement	TT PRO 250	
Connected air duct size	mm	250	
Speed	-	2	
Minimum supply voltage	V	230	
Maximum supply voltage	V	230	
Power supply frequency	Hz	50/60	
Rated power	W	125	177
Unit current	A	0.54	0.79
Maximum airflow	m ³ /h	1110	1400
Sound pressure level LpA at 3 m	dB(A)	44	51
Weight	kg	7.8	
Transported air temperature (max)	°C	60	
Ingress protection rating	-	IPX4	
Ingress protection rating of the drive	-	IPX4	
ErP compliance	-	2016, 2018	
Unit category	-	NRVU	
Type of drive installed	-	External MSD or VSD	
Type of heat recovery system	-	None	
Nominal flow rate	m ³ /s	0.206	
Nominal external pressure	Pa	247	
Maximum external leakage rates	%	2.7	
Static efficiency	%	31.5	

Declared typology	-	NRVU UVU
Sound power level	dB(A)	72
Effective electric power input	kW	0.165

Dimensions

$\varnothing D$	B	H	L
247	287	323	383

